



**SBA WOSB**  
Woman Owned Small Business



For more information:  
Call: (800) 930-0901  
Email: [sales@BarrierHQ.com](mailto:sales@BarrierHQ.com)  
Web: [www.BarrierHQ.com](http://www.BarrierHQ.com)

# BI-DIRECTIONAL LIGHT

## TYPE A: FLASHING

## TYPE C: STEADY BURN

**Red Lens SKU: BDL-AC-R**

**Yellow/Amber Lens SKU: BDL-AC-Y**

One of our most innovative hazard lights yet, the Type A/C solar-powered Bi-Directional Barricade Light (BDL) was reimagined to leverage improved battery technology and solar panel efficiency in order to provide an easy-to-install product that exceeds industry requirements.

## FEATURES & BENEFITS

- 3-Way Switch: Auto Flashing, Auto Steady, Off
  - 1st Press: Auto Flashing
  - 2nd Press: Auto Steady
  - 3rd Press: OFF
  - (Light turns on automatically during low-light conditions)
- High-efficiency solar panel
- Preinstalled NiMH Rechargeable Batteries
  - >730 recharging cycles
- Full Battery Charge: Operates for 120+ Hours (Flashing), 72+ Hours (Steady)
- Operating Temperature Range: -20°F to +150°F / -29°C to +65°C
- Water and dust resistant to IP65 standard
- Also Included: mounting bolt, mounting bolt spacer, wire switch key, anti-rotation bracket

## HAZARD LIGHT OUTPUT

- Type A Minimum Luminous Intensity: 4.0 candela (Yellow) / 1.0 candela (Red)
- Type C Minimum Luminous Intensity: 2.0 candela (Yellow and Red)
- Minimum Visible Distance: 900m (3,000 ft) on a clear night

## COMPATIBLE WITH

- OTW32x45
- OTW42x72 (\*)
- Most A-Frames (\*\*)
- Most Vertical Panels
- Most Traffic Delineators
- Most Traffic Drums

(\*) Requires mounting bolt spacer (included)

(\*\*) Requires anti-rotation bracket (included)

## GOVERNMENT/INDUSTRY STANDARDS

- Meets or Exceeds UDOT Standards
- Meets or Exceeds MUTCD Requirements
- Meets or Exceeds ITE Specifications



## FLASH RATE

- 65 per minute

## LENS COLOR

- Yellow/Amber or Red



## SIZE

- 280 x 200 x 76mm / 11 x 7.5 x 3in

## WEIGHT

- 580g / 20.5oz / 1.28 lbs

## BATTERY LIFE

- 120+ Hours (Flashing)
- 72+ Hours (Steady)